




ACJT210-8W 2A TRIAC

Rev.A.1.1

DESCRIPTION:

The ACJT210-8W triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. The ACJT210-8W embeds a TVS structure to absorb the inductive turn-off energy such as those described in the IEC 61000-4-5 standards. Package SOT-223-2L is RoHS compliant.




MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T <sub>stg</sub>	-40-150	
Operating junction temperature range	T <sub>j</sub>	-40-125	
Repetitive peak off-state voltage (T <sub>j</sub> =25 )	V <sub>DRM</sub>	800	V
Repetitive peak reverse voltage (T <sub>j</sub> =25 )	V <sub>RRM</sub>	800	V
		2	A

ACJ

ORDERING INFORMATION



MARKING




FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature




FIG.3: RMS on-state current versus ambient

$p(er)4.5 ( )TJ /C2T3 1 Tf -0.011 Tc 01105 Tw 0 -17789 TD<0.0728> ^2\epsilon \& ( b\epsilon$

FIG.7: Relative variations of gate trigger current, holding current and latching current versus junction temperature





FIG.8 ÖTest circuit for inductive and resistive loads to IEC-61000-4-5 standards



ACJT210-8W

PACKAGE MECHANICAL DATA





